

Single-Line Concentrate Doorway Foam Unit



DS3



Features

- Draws from concentrated product
- Dilutes product at ratios of 38:1 to 183:1 (water:chemical)
- Repeat cycle timer
- Quick-change pump
- Supports up to 2 nozzle assemblies
- Up to 25 ft (7.6 M) total distance between control box and nozzle(s)
- Consistent, reliable dilution rates, regardless of changes in water pressure

Industries

- Institutional
- Food and beverage
- Manufacturing



how to buy

The Good Stuff

- **Consistent dilution rates**
Regardless water pressure changes, this unit reliably dilutes chemistry
- **Nozzle assembly**
Supports up to 2 nozzle assemblies with a total of 25ft (7.6 m) total distance between control box and nozzle(s)
- **On schedule chemical delivery**
Repeat cycle timers (adjustable via traffic flow) set delays to ensure coverage

Specs

- Power type compressed air, electricity
- Chemical pickup type draws from concentrated product
- Dilution ratio range (water:chemical) 38:1 to 183:1
- Number of products unit can draw from one product
- Suction line length/diameter 8 ft. (2.4 m) clear hose with 1/4 in. (6.4 mm) inside diameter
- Flow rate 2 gal/min (7.6 l/min)
- Pump seals Santoprene, Viton, or Kalrez
- Timer operation type repeat cycle
- Coverage area ONE NOZZLE: up to 9×4 ft. (2.7×1.5 m); TWO NOZZLES: up to 5×3 ft. (2.4×1.2 m) at each nozzle
- Nozzle type single-line nozzle assembly (NZA-DS-SL)
- Number of nozzles one control box can support up to two nozzle assemblies
- Distance from nozzles to control box the combined distance between the control box and nozzle(s) must equal 25 ft. (7.6 m) or less
- Tubing/fitting sizes designed for use with 1/2 in. (12.7 mm) outside diameter tubing between control box and nozzle(s)

Requirements

- Compressed air requirements 40-80 psi (2.8-5.5 bar) with 5-10 cfm (141.6-283.2 l/min)
- Water requirements 10-100 psi (0.7-6.9 bar) backflow prevention is required
- Liquid temperature range 40-100 ° F (4.4-37.8 ° C)
- Electrical requirements 120 VAC at 60 Hz, 2 amps (GFCI protected outlet)
- Operating voltage 120 VAC
- Chemical compatibility chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.