

20 Gallon Portable Fog Unit With Timer

FG-20N-3-TM



Features

- Easy-to-use delay timer
- 3 Nozzles mounted on fog mast
- See through tank – 20 gallon (75.7 liter) capacity
- Quick-change pump
- Hinged back plate provides tool-free access to components
- Hinged lid, so you will never lose it
- Front-facing drain for easy tank drainage
- In-line strainer to protect pump from debris

Options

- Color coding
 - Lid – 9 colors (BK, BL, BN, GN, OR, PL, RD, WH, YL)
- Pump seals
 - Santoprene, Viton, or Kalrez

Industries

- Institutional
- Food and beverage
- Manufacturing



how to buy

The Good Stuff

- **Efficient air consumption**
Uses approx. 9 CFM, 80% more efficient than our competitors
- **Telescoping fogging mast**
Insures fog chemistry fills a space, large or small
- **Delay timer**
Timer version for situations where personnel need to be cleared from a space and/or for overnight cleaning

Specs

- Power type compressed air and electricity
- Chemical pickup type draws from pre-mixed solution
- Number of products unit can draw from one product
- Capacity 20 gallons (75.7 liters)
- Flow rate 3.7 gallons/hour per nozzle
(11.1 gallons/hour total with 3 nozzles)
- Pump seals Santoprene, Viton, or Kalrez
- Timer operation type single shot timer with delay
- Droplet size 15 microns at 50 psi (3.4 bar)
- Coverage area 1 liter of solution will cover
approx. 1000 cubic feet
- Product height 47 inches (119.3 cm)
- Run time from full tank approx. 2 hours
- Nozzle type pneumatic fog nozzle
- Number of nozzles 3
- Fog mast height range 3.5-8.5 ft. (1.1-2.6 m)
- Wheel type two 10 in. (25.4 cm) non-marking wheels

Requirements

- Compressed air requirements 50 psi (3.4 bar) with
9 CFM (254.9 l/min)
- Liquid temperature range 40-100 ° F (4.4-37.8 ° C)
- Electrical requirements 120 VAC at 60 Hz, 2 amps
(GFCI protected outlet)
- Operating voltage 120 VAC
- Chemical compatibility chemical products
used with this equipment must be formulated for this type of
application and compatible with unit materials and pump seals. For
more information on chemical compatibility, consult the manufacturer
or SDS for your product or contact our customer service department.

