

15 Gallon Battery Foam Unit

FI-BP-15N-BSLA



Features

- Designed for easy charging and maintenance
- Draws from pre-mixed solution
- Battery-powered
 - Up to 2 hours of non-continuous run time from one charge
- Easy-to-read battery level indicator on back plate
- Hinged lid
- In-line strainer to protect pump from debris
- Ideal for drain foaming, spot cleaning, and more
- Produces lower volume of foam than our air-operated units

Options

- Color coding
 - Lid – 9 colors (BK, BL, BN, GN, OR, PL, RD, WH, YL)
 - Discharge hose – 4 colors (BL, GN, YL, RD)

Industries

- Institutional
- Food and beverage
- Manufacturing



how to buy



800 567 5420 | sales@foamit.com

The Good Stuff

- **Battery powered**
No air lines or power cords to hold you back, and an easy-to-read battery level indicator on the back plate
- **Easy charging and maintenance**
Designed for portability, efficiency, and hassle-free maintenance. Our quick-change pump and tool-free, hinged access plate reduce downtime when a repair is needed
- **Natural color tank**
See chemical volume levels at a glance

Specs

- Power typeSLA battery
- Battery charge time (from full depletion)7.5 hours
- Battery run time (from full charge)up to 2 hours of non-continuous run time
- Chemical pickup typedraws from pre-mixed solution
- Suction line diameter3/8 in. (9.5 mm) inside diameter
- Number of products unit can draw fromone product
- Capacity15 gallons (56.8 liters)
- Discharge hose diameter/length15 ft. (4.6 m) hose, with 1/2 in. (12.7 mm) inside diameter
- Discharge wand/tip typestainless steel wand with 65° fan tip fan and ball valve
- Output distance5-6 ft. (1.5-1.8 m)
- Output volume4-5 gal/min (15.1-18.9 l/min) of foam
- Flow rate2 gal/min (7.6 l/min)
- Pump sealsSantoprene, Viton, or Kalrez
- Wheel typetwo 10 inch (25.4 cm) non-marking wheels

Requirements

- Liquid temperature range40-100 °F (4.4-37.8 °C)
- Electrical requirements120 VAC at 60 Hz, 2 amps (GFCI protected outlet) for battery charger only
- Operating voltage12 VDC
- Chemical compatibilitychemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.